



NHC SERIES NO HUB MECHANICAL JOINT (MJ) COUPLING


Specification:

- Shielded couplings for joining hubless cast iron pipe and fittings in drain, waste and vent (DWV) piping applications.
- Flexible neoprene gasket manufactured in compliance with ASTM C564
- Max Test Pressure: 4.3 PSI (29.6KPA)
- Max Operating Temperature: 140°F (60°C)
- Min Operating Temperature: -30°F (-34°C)
- Includes two 300 Stainless Steel clamps and corrugated shield



Certification:

- UPC Certified to ASTM C1277 & CSA B602 Standards



DIMENSIONS								
Part No.	Connection Sizes	A		B		C		Weight grams
		inches	mm	inches	mm	inches	mm	
NHC-15	1-1/2" C.I. / PL	1.90	48.00	1.90	48.00	2.12	54.00	110
NHC-20	2" C.I. / PL	2.40	61.00	2.40	61.00	2.12	54.00	130
NHC-2015	2" x 1-1/2" C.I. / PL	2.40	61.00	1.90	48.00	2.12	54.00	170
NHC-30	3" C.I. / PL	3.50	89.00	3.50	89.00	2.12	54.00	170
NHC-40	4" C.I. / PL	4.50	114.00	4.50	114.00	2.12	54.00	205
NHC-50 **	5" C.I. / PL	5.56	141.00	5.56	141.00	2.98	76.00	420
NHC-60 **	6" C.I. / PL	6.56	166.00	6.56	166.00	2.98	76.00	500

** Come with 4 clamps joined to shield



25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164

www.boshart.com