



INFINITE USES AND COUNTING!

Doors hinges, lawnmowers, tents...



Can I Jig-A-Lo it?

JIG-A-LOO ▾ NANO ▾ GARAGE DOOR LUBRICANT ▾ PERFORMA PTFE ▾ GRAPHITE EXTREME ▾ WHITE LITHIUM ▾ LUBRI PENETRA ▾ JIG-A-CLEAN ▾



JIG-A-LOO

## THE INVISIBLE ALL AROUND LUBRICANT

Jig-A-Lo is a revolutionary product that combines the power of a lubricant with the properties of a water-repellent!

Tweet

Recommend 26

Share



### MORE INFORMATION



Download product PDF MSDS

### WHAT IS JIG-A-LOO?

Jig-A-Lo is unlike any other lubricant - it contains no oil, grease, wax, petroleum distillates or detergent; it is colorless and won't stain. It stops squeaks, un-sticks just about anything, protects against rust and is an exceptional water repellent and more.

Jig-A-Lo is ideal for wood, metal, glass, rubber, leather, fabrics, most plastics and a number of other surfaces. Helping just about anything operate and slide better with its thousands of uses, it's the can of all trades™.

Some plastics and painted surfaces may be damaged with contact. Please check before using.

- Contents under pressure.
- Flammable aerosol.
- Vapor may be harmful & flammable.
- May cause cancer.
- Irritates eyes, skin and respiratory tract.
- Harmful if swallowed.
- Contact with flame or hot surfaces may cause toxic gases.

#### Precautions:

Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Do not smoke. Use only with adequate ventilation. Do not breathe vapors, spray mist, or over spray. Ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. Do not puncture or incinerate container or store at temperature over 50°C. Container may explode if heated.

#### First aid:

Eyes: immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, do not delay flushing or attempt to remove the lens. If irritation or pain persists, see a doctor.

Skin: take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately flush with lukewarm, gently flowing water for 15-20 minutes. Call a poison centre or doctor. Double bag, seal, label and leave contaminated clothing, shoes and leather goods at the scene for safe disposal. Inhalation: if affected by inhalation of vapour or spray mist, remove to fresh air.

Ingestion: have victim rinse mouth with water. Immediately call a poison centre or doctor. Contains (cas no.): methylene chloride (75-09-2), perchloroethylene (127-18-4), isobutane (75-28-5) and propane (74-98-6).

Refer to material safety data sheet

Keep out of reach of children

#### Directions for use:

- For best results, shake well
- Hold upright, point nozzle at target from a distance of 15 cm and spray
- Use regularly

Model JIG1601, net weight: 10.9 oz. (311 g)

Model JIG701, net weight: 5.5 oz. (155 g)

Model JIG501 net weight: 3.0 oz. (85 g)

Made in Canada with domestic and imported parts

Net weight: 10.9 oz. (311g)



### SAMPLE OF JIG-A-LOO USES

**USE N°12**  
Cleans and protects cables and connectors



**USE N°20**  
Cleans and protects trailer hitch locking mechanism



**USE N°23**  
Cleans burnt oil from exhaust pipes on motorcycles



**USE N°27**  
Cleans gunk and compressor oil off pistons in solenoids



**USE N°28**  
Cleans gunk from travel trailer siding



**USE N°29**  
Cleans gunk off snow chains



### HAVE AN UNUSUAL AMOUNT OF TIME ?

See all uses



#### NEWSLETTER

Sign up for the latest news and promotions from JIG-A-LOO !

E-mail

SEND

#### OUR PRODUCTS

- Jig-A-Lo
- White Lithium
- Graphite Extreme
- Performa PTFE
- Lubri Penetra
- Jig-A-Clean

#### SITE MAP

TERMS & CONDITIONS  
USES

#### FRANÇAIS