# Technical Information Bulletin



Nominal length : 48 in. (1 200 mm) Dia. : 1 in. (26 mm)

## Choice LED Linear \_\_

Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

#### ORDERING INFORMATION

Order code:

T8/S2/10.5W/840/48/CHOICE/STD **Description:** 

UPC: 069549679733

Case quantity:

#### PHYSICAL DATA

T8 Shape: G13 Base: Material: Glass

### PERFORMANCE DATA

Bare Lamp Watts (W): 10.5

Volts (VAC): 120 -277/347 Colour temperature (K)1: 4 000

Life L70 (hrs): 50 000 82

Starting method: Instant start

Operating temperature range: -20°C/ -4°F to 40°C/104°F

Order code	Average System Watts (W)			Initial Lumens (Im) <sup>2</sup>		(lm)²
	LBF	NBF	HBF <sup>3</sup>	LBF	NBF	HBF <sup>3</sup>
67977	11.5	13	17	1 600	1 800	2 400

<sup>&</sup>lt;sup>1</sup> Typical colour temperature range: +/- 5 % 1 Typical colour temperature range: +/- 10 % <sup>2</sup> LBF= Low ballast factor, NBF= Normal ballast factor, HBF= High ballast factor











Please refer to the ballast compatibility list to confirm lamp compatibility with the existing luminaire.

#### **CAUTIONS**

THIS LAMP OPERATES ON INSTANT START ELECTRONIC BALLASTS. Direct replacement for 32W/48 T8 only.

Qty	Description	Price
I accept the spe	ecifications of the luminaire configuration me	entioned above.
Name:		
Company:		
Signature:		Date:



